

## ZB5FG8

flush mounted selector switch head key 455 3  
pos return right to center



### Main

|                               |                               |
|-------------------------------|-------------------------------|
| Range of product              | Harmony XB5                   |
| Product or component type     | Head for key selector switch  |
| Device short name             | ZB5                           |
| Bezel material                | Dark grey plastic             |
| Mounting diameter             | 30 mm                         |
| Head type                     | Built-in-flush                |
| Sale per indivisible quantity | 1                             |
| Shape of signaling unit head  | Round                         |
| Type of operator              | Right to centre spring return |
| Operator profile              | Black key switch              |
| Operator position information | 3 positions +/- 45°           |
| Type of keylock               | Ronis 455                     |
| Key withdrawal position       | Center                        |

### Complementary

|                             |   |
|-----------------------------|---|
| CAD overall width           | 37 mm   |
| CAD overall height          | 37 mm   |
| CAD overall depth           | 72 mm   |
| Net weight                  | 0,069 kg  |
| Mechanical durability       | 1000000 cycles  |
| Electrical composition code | C4 6 single and double front mounting<br>C5 5 single front mounting<br>C6 5 single and double front mounting<br>C7 4 single front mounting<br>C8 4 single and double front mounting<br>C11 3 single front mounting<br>C3 6 single front mounting<br>SF1 3 single front mounting |

### Environment

|                                       |   |
|---------------------------------------|---|
| Protective treatment                  | TH                                      |
| Ambient air temperature for storage   | -40...70 °C                             |
| Ambient air temperature for operation | -40...70 °C                             |
| Overvoltage category                  | Class II IEC 60536                      |
| IP degree of protection               | IP66 IEC 60529<br>IP67<br>IP69<br>IP69K |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                      |
| Resistance to high pressure washer    | 7000000 Pa 55 °C 0.1 m                  |
| IK degree of protection               | IK03 IEC 50102                          |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                        |   |
|------------------------|---|
| Standards              | JIS C8201-5-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>CSA C22.2 No 14<br>UL 508<br>JIS C8201-1 |
| Product certifications | LROS (Lloyds register of shipping)<br>UL listed<br>GL<br>DNV<br>BV<br>RINA<br>CSA                                   |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6   |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Status održive ponude      | Proizvod Green Premium   |
| Uredba REACh               | <a href="#">Izjava REACh</a>   |
| REACh, bez SVHC            | Da   |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Bez otrovnih teških metala | Da   |
| Bez žive                   | Da   |
| Informacije o RoHS izuzeću | <a href="#">Da</a>   |
| Propis RoHS za Kinu        | <a href="#">Izjava RoHS Za Kinu</a>  |
| Izjava o očuvanju okoliša  | <a href="#">Ekološki Profil Proizvoda</a>  |
| Profil cirkularnosti       | <a href="#">Informacije O Kraju Vijeka Trajanja</a>  |