

## Product data sheet

### Characteristics

## ZB5AG514

glava izborne preklopke Ø 22, 3 položaja  
nepomična Ronis 520E



### Main

|                               |                              |
|-------------------------------|------------------------------|
| Range of product              | Harmony XB5                  |
| Product or component type     | Head for key selector switch |
| Device short name             | ZB5                          |
| Bezel material                | Dark grey plastic            |
| Mounting diameter             | 22 mm                        |
| Head type                     | Standard                     |
| Sale per indivisible quantity | 1                            |
| Shape of signaling unit head  | Round                        |
| Type of operator              | Stay put                     |
| Operator profile              | Black key switch             |
| Operator position information | 3 positions +/- 45°          |
| Type of keylock               | Ronis 520E                   |
| Key withdrawal position       | Left and right               |

### Complementary

|                             |                                                                                                                                                                                                                                                                                                               |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 29 mm                                                                                                                                                                                                                                                                                                         |
| CAD overall height          | 29 mm                                                                                                                                                                                                                                                                                                         |
| CAD overall depth           | 72 mm                                                                                                                                                                                                                                                                                                         |
| Net weight                  | 0,057 kg                                                                                                                                                                                                                                                                                                      |
| Mechanical durability       | 1000000 cycles                                                                                                                                                                                                                                                                                                |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                                                                                                                                    |
| Electrical composition code | C4 6 single and double front mounting<br>C5 5 single front mounting<br>C6 5 single and double front mounting<br>C7 4 single front mounting<br>C8 4 single and double front mounting<br>C11 3 single front mounting<br>C3 6 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting |
| Device presentation         | Basic element                                                                                                                                                                                                                                                                                                 |

### Environment

|                                       |                                         |
|---------------------------------------|-----------------------------------------|
| Protective treatment                  | TH                                      |
| Ambient air temperature for storage   | -40...70 °C                             |
| Ambient air temperature for operation | -40...70 °C                             |
| Overvoltage category                  | Class II IEC 60536                      |
| IP degree of protection               | IP66 IEC 60529<br>IP67<br>IP69<br>IP69K |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                      |
| Resistance to high pressure washer    | 7000000 Pa 55 °C 0.1 m                  |

|                         |                                                                                                                     |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|
| IK degree of protection | IK06 IEC 50102                                                                                                      |
| Standards               | JIS C8201-5-1<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-5-4<br>JIS C8201-1 |
| Product certifications  | DNV<br>UL listed<br>LROS (Lloyds register of shipping)<br>BV<br>CSA<br>GL<br>RINA                                   |
| Vibration resistance    | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                       |
| Shock resistance        | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |

### Offer Sustainability

|                            |                                                                                                                                                                                            |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                                                                                                     |
| Uredba REACh               |  <a href="#">Izjava REACh</a>                                                                             |
| REACh, bez SVHC            | Da                                                                                                                                                                                         |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS)  <a href="#">Izjava EU RoHS</a> |
| Bez otrovnih teških metala | Da                                                                                                                                                                                         |
| Bez žive                   | Da                                                                                                                                                                                         |
| Informacije o RoHS izuzeću |  <a href="#">Da</a>                                                                                       |
| Propis RoHS za Kinu        |  <a href="#">Izjava RoHS Za Kinu</a>                                                                    |
| Izjava o očuvanju okoliša  |  <a href="#">Ekološki Profil Proizvoda</a>                                                              |
| Profil cirkularnosti       |  <a href="#">Informacije O Kraju Vijeka Trajanja</a>                                                    |

### Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|