



Komercijalni status

Više se ne proizvodi: 20 prosinac 2020

Main

Range	Altira
Product or component type	Socket-outlet
Range compatibility	fixing frame fixing frame
Device presentation	Mechanism
Number of power socket outlets	1 x 2P + E, German
Outlet standard description	Side earth
Socket additional information	Shuttered
Colour tint	Cover plate polar white RAL 9003)

Complementary

Product destination	Fixing frames
Range compatibility	OptiLine 70 with Altira adaptor OptiLine 45
Ground lug position	Slanted 45° position
Rated current	16 A 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Connections - terminals	Screwless terminals
Clamping connection capacity	4 x 1.5...4 x 2.5 mm ² rigid 4 x 1.5...4 x 2.5 mm ² solid stranded
Material	PC mechanism cover
Surface treatment	Untreated
Surface finish	Satin
Product compatibility	Altira fixing frame
Standards	EN 62262 IEC 60884-1 NF C 61-314 EN 60529

Height	45 mm
Width	45 mm
Depth	39 mm
Net weight	0,032 kg

Environment

Ambient air temperature for operation	5...50 °C
Ambient air temperature for storage	-15...60 °C
IK degree of protection	IK02
IP degree of protection	IP20
Environmental characteristic	Oil Liquid soap Alcohol UV resistant Ammonia Petrol Window-cleaning fluid Hydrogen peroxide (H2O2) Bleach Acetone
Environmental health and issues	Halogen free

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS za Kinu Proizvod izvan dosega propisa RoHS za Kinu. Informativna deklaracija o tvarima.
Izjava o očuvanju okoliša	Ekološki profil proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja

Contractual warranty

Jamstvo	18 months
---------	-----------