

Rittal – The System.

Faster – better – everywhere.

Kompaktni rasklopni ormari AE – AE 1360.500

Date : 2018.12.07

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Kompaktni rasklopni ormari AE – AE 1360.500

created: 07.12.2018 build on www.rittal.com/hr-hr



Product description

Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
IK Code:	IK08
Supply includes:	Montažna ploča
Basic material:	Čelični lim

Product features

Dimensions:	Width: 600 mm Height: 600 mm Depth: 350 mm
Material thickness:	Enclosure: 1,5 mm Door: 1,75 mm Mounting plate: 2,5 mm
Mounting plate:	Width: 549 mm

Height: 570 mm

Number of doors:	1
Door hinged on the right, may be swapped to the left:	da
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Gland plate, size:	5
Gland plate, qty.:	1
Packs of:	1 pc(s).
Weight/pack:	28,4 kg
EAN:	4028177252493
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	AE Compact enclosure, WHD: 600x600x350 mm, Sheet steel, with mounting plate, single-door, with two cam locks

Approvals

Approvals:
CSA
DNV-GL
Lloyds Register of Shipping
RRR
Russian Maritime Register of Shipping
TÜV

Certificates:	EAC IK-Code Protection category
Declarations:	Declaration of conformity