

## Product data sheet

### Characteristics

# MGU3.213.18

Unica – ozibna sklopka – 2x2-položaja – 10 AX  
250 V AC – 2 m – bijela



### Main

|                           |                            |
|---------------------------|----------------------------|
| Range of product          | Unica                      |
| Aesthetic name            | Unica (standard aesthetic) |
| Product or component type | Switch                     |
| Device presentation       | Mechanism                  |
| Switch function           | 1-pole 2-way               |
| Number of rocker          | 2                          |
| Device application        | Control                    |
| Provided equipment        | Internal power connection  |
| Colour tint               | White                      |

### Complementary

|                                       |                                                                   |
|---------------------------------------|-------------------------------------------------------------------|
| Rated current                         | 10 AX 250 V AC 50/60 Hz                                           |
| Electrical durability                 | 10000 cycles                                                      |
| Insulation resistance                 | > 5 MOhm 500 V                                                    |
| Dielectric strength                   | 2000 V                                                            |
| Minimum load breaking capacity        | 200 operations 1.25 In and 1.1 Un, cos phi = 0,3                  |
| Opening distance                      | > 3 mm                                                            |
| Actuator                              | Rocker                                                            |
| Number of modules                     | 2 modules                                                         |
| Connections - terminals               | Screwless terminals                                               |
| Cable cross section                   | 0...2,5 Mm <sup>2</sup> rigid<br>0...2,5 mm <sup>2</sup> flexible |
| Material                              | ASA + PC mechanism cover                                          |
| Fixing mode                           | Clip-in                                                           |
| Width                                 | 45 mm                                                             |
| Height                                | 45 mm                                                             |
| Depth                                 | 34 mm                                                             |
| Embedding depth                       | 22 mm                                                             |
| Net weight                            | 0,039 kg                                                          |
| Ambient air temperature for operation | 25...35 °C                                                        |
| Ambient air temperature for storage   | 0...50 °C                                                         |
| Standards                             | EN 60669-1<br>EMC directive<br>LV directive                       |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                 |                                                                                                                  |
|---------------------------------|------------------------------------------------------------------------------------------------------------------|
| IP degree of protection         | IP20                                                                                                             |
| IK degree of protection         | IK01                                                                                                             |
| Environmental characteristic    | Petrol<br>UV resistant<br>Bleach<br>Acetone<br>Ammonia<br>Oil<br>Window-cleaning fluid<br>Liquid soap<br>Alcohol |
| Environmental health and issues | Halogen free                                                                                                     |

## Offer Sustainability

|                            |                                                                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                                                               |
| Uredba REACh               | <a href="#">Izjava REACh</a>                                                                                                                         |
| REACh, bez SVHC            | Da                                                                                                                                                   |
| Direktiva EU RoHS          | Sukladno <a href="#">Izjava EU RoHS</a>                                                                                                              |
| Bez otrovnih teških metala | Da                                                                                                                                                   |
| Bez žive                   | Da                                                                                                                                                   |
| Informacije o RoHS izuzeću | <a href="#">Da</a>                                                                                                                                   |
| Propis RoHS za Kinu        | <a href="#">Izjava RoHS Za Kinu</a>                                                                                                                  |
| Izjava o očuvanju okoliša  | <a href="#">Ekološki Profil Proizvoda</a>                                                                                                            |
| Profil cirkularnosti       | Nema potrebe za specifičnim operacijama recikliranja                                                                                                 |
| WEEE                       | Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom. |

## Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|