

Product data sheet

Characteristics

MGU3.283.18

Unica – sklopka za ključ-kartice – 10 A – 230 V
AC – 2 m – bijela



Main

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Key card switch
Device application	Control
Device presentation	Mechanism
Cover plate colour tint	White

Complementary

[Ue] rated operational voltage	230 V AC +/- 10 % 50 Hz
Rated current	10 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Condition of use	Control through appropriate relay
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Fuse type	Electronic
Maximum number of switchings	50000 operations
Pilot light	Locator lamp
Marking	Vertical insertion pictogram
Connections - terminals	Soldered connectors
Clamping connection capacity	<= 1 x 2.5 mm ² flexible <= 1 x 2.5 mm ² rigid
Fixing mode	Clip-in
Material	ASA + PC mechanism cover
Embedding depth	14 mm
Depth	Unica Basic cover frame 36 mm Unica Colors cover frame 36 mm Unica Allegro cover frame 35 mm Unica Plus cover frame 35 mm
Width	45 mm
Height	45 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Bleach Oil Alcohol Acetone Window-cleaning fluid Petrol Ammonia Liquid soap UV resistant
Environmental health and issues	Halogen free
Standards	EN 61058-1

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACh	Izjava REACh
REACh, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------