



22003001

General information	
Product Range:	SIRCO M
Long Description:	AC SWITCH DISCONNECT, SIRCO M 20A 3P, UL508, Direct or external operation, DIN rail or base mount, Handle, shaft and other accessories not included
Short Description:	SIRCO M1 3X20A

Certificates and declaration

Conformity to standard #1:	UL508
Conformity to standard #4:	E173959 Vol. 1 Sec. 1

Container Information

EAN13:	3596031825387
Package Level 1 Gross Weight:	0.21
Package Level 1 Length:	0.1
Package Level 1 Units:	B
Package Level 1 Width:	0.08

Main

Reference:	22003001
------------	----------

Ordering

country of origin:	CN
--------------------	----

Technical characteristics

Connection terminals

Solid - 1 wire:	#14 - #10
Solid - 2 wires:	2 x #12
Stranded - 1 wire:	#14 - #4
Stranded - 2 wires:	2 x (#14 - #12)

Max. motor HP

FLA 3 ph motor max. / 208 VAC:	5/16.7
FLA 3 ph motor max. / 220-240 VAC:	5/15.2
FLA 3 ph motor max. / 440-480 VAC:	10/14
FLA 3 ph motor max. / 600 VAC:	15/17

Mechanical characteristics

Endurance (number of operating cycles):	10000
Operating torque (lbs.in?/?Nm):	7/0.8

Short-circuit capacity

Max fuse rating (A):	30
Short circuit rating at 600 VAC (kA):	65
Type of fuse:	J

Auxiliary contacts / Electrical characteristics:	A300
Number of Poles:	3
UL General use rating (A):	20