Product datasheet Characteristics

NSYS3X3315

SPACIAL S3X stainless 304L, Scotch Brite® finish, H300xW300xD150 mm.

Price*: 156.18 GBP



Range	Spacial	
Product name	Spacial S3X	
Enclosure type	Multi-purpose	
Category	Compact enclosure	
Nominal height	300 mm	
Nominal width	300 mm	
Nominal depth	150 mm	
Product installation	Wall-mounting	
Device composition	1 body	
	1 door	
	1 lock (door)	

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face : 1 door(s)	
Door opening side	120°, reversible	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door fixing: by hinges	
Material	Lock : zamak Hinge : stainless steel Body and door : stainless steel 304L	1
Surface finish	Lock : chromium plated Body and door : Scotch-Brite® brushed	
Thickness	1.5 mm	
Product weight	4.062 kg	

Environment

Standards	IEC 62208
Product certifications	CAN/CSA 22 UL 508 type A
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Environmental characteristic	Corrosive Specific hygiene

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months 18 months