# Product data sheet Characteristics

# NSYSBM404012

Metal industrial box plain door H400xW400xD120 IP66 IK10 RAL 7035





#### Main

Range	Spacial		
Product name	Spacial SBM		
Device application	Multi-purpose		
Category	Industrial box		
Device short name	SBM		
Enclosure type	Flat face box		
Enclosure nominal height	400 mm		
Enclosure nominal width	400 mm		
Enclosure nominal depth	120 mm		
Enclosure mounting	Wall mounted		
Device composition	4 cover screw		
	1 cover		
	1 body		
Body type	Single piece body folded and welded		
Type of front cover	Plain door		
Cover fixing	Half turn metal screw		
Lock type	Captive screw PZ2 outside sealed area		
Removable parts	Cover by captive screws		

#### Complementary

Material	Sheet steel	n <del>te</del>
Surface finish	Polyester powder	not
Colour	Grey (RAL 7035)	.s. .o.
Standards	IEC 62208	en dat
Product certifications	GL BV DNV LR	aimer: This docum

UL

IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Ambient air temperature for storage	-3560 °C	
Operating temperature	-3580 °C	
Net weight	5.364 kg	

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.364 kg
Package 1 Height	43 cm
Package 1 width	43 cm
Package 1 Length	14.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information		
Environmental Disclosure	Product Environmental Profile		

## Contractual warranty

Warranty	18 months	