



Main

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing self-extinguishing engineering polymer
Contacts material	Sleeves brass
Connections - terminals	Captive screws
Cable cross section	1...4 mm ²
Cable outer diameter	8...15 mm
Cable entry	Fair lead Cable gland
Thread type	Pg 21
Product weight	0,16 kg
Height	78 mm
Width	78 mm
Depth	140 mm
Colour	Grey RAL 7035)
Voltage colour	Blue

Environment

Standards	IEC 60309-1
-----------	-------------

IEC 60309-2

IP degree of protection	IP44 IEC 60529
IK degree of protection	IK08 EN 62262
Fire resistance	850 °C IEC 60695-2-1
Relative humidity	50 % 40 °C 70 % 30 °C 90 % 20 °C
Ambient air temperature for operation	35 °C 86400 s) -25...40 °C

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	 Izjava REACH
Direktiva EU RoHS	Pro-active compliance (Product out of EU RoHS legal scope)  Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	 Da
Propis RoHS za Kinu	 Izjava RoHS za Kinu
Izjava o očuvanju okoliša	 Ekološki profil proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja

Contractual warranty

Jamstvo	18 months
---------	-----------