



Main

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa screw
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight
[In] rated current	32 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing self-extinguishing engineering polymer
Contacts material	Sleeves brass
Connections - terminals	Captive screws
Cable cross section	2,5...10 mm ²
Cable outer diameter	11,5...21 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 21
Neto težina	0,25 kg
Maksimalna visina	98 mm
Maksimalna širina	98 mm
Maksimalna dubina	165 mm

Izjava: Ovi dokumenti ne mijenjaju niti su namijenjeni utvrđivanju primjerenosti ili pouzdanosti ovih proizvoda u specifičnim korisničkim primjenama.

Colour	Sivo RAL 7035)
Voltage colour	Blue

Environment

Standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 IEC 60529
IK degree of protection	IK08 EN 62262
Fire resistance	850 °C IEC 60695-2-1
Relative humidity	50 % 40 °C 70 % 30 °C 90 % 20 °C
Ambient air temperature for operation	35 °C 86400 s) -25...40 °C

Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Broj pakirnih jedinica u Paketu 1	1
Paket 1 Težina	223 g
Paket 1 Visina	6,5 cm
Paket 1 Širina	9,5 cm
Paket 1 Duljina	17 cm
Vrsta pakirne jedinice Paketa 2	BB1
Broj pakirnih jedinica u Paketu 2	10
Paket 2 Težina	2,398 kg
Paket 2 Visina	26 cm
Paket 2 Širina	17 cm
Paket 2 Duljina	27 cm
Vrsta pakirne jedinice Paketa 3	S03
Broj pakirnih jedinica u Paketu 3	20
Paket 3 Težina	5,283 kg
Paket 3 Visina	30 cm
Paket 3 Širina	30 cm
Paket 3 Duljina	40 cm

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Direktiva EU RoHS	Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS za Kinu Proizvod izvan dosega propisa RoHS za Kinu. Informativna deklaracija o tvarima.
Izjava o očuvanju okoliša	Ekološki profil proizvoda

Contractual warranty

Jamstvo	18 months
---------	-----------