## CABS Module Kit – CABS2-10T-MOD (549380)












- Modules provide flexibility to select distance between phases and supports
- Installs quickly and easily
- Halogen free insulators
- RoHS compliant







Part Number	CABS2-10T-MOD
Article Number	549380
Material	Steel Glass Fibre Reinforced Polyamide
Finish	Electrogalvanized
Typical Application Current Rating	400 – 4.500 A
Max Working Voltage, IEC (Ui)	1.000 VAC 1.500 VDC
Working Temperature	-40 to 130 °C
Complies With	IEC® 60439.1 IEC® 61439.1 IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating	UL® 94V-0
Busbars per Phase	1 – 2
Busbar Width	30 – 120 mm
Busbar Thickness	10 mm
Depth (D)	39 mm
Width (W)	75 mm
Unit Weight	0,37 kg
Certifications	CE, ERIFLEX CABS EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS



Part Number	CABS2-10T-MOD
Standard Packaging Quantity	1 рс
UPC	78285669121
EAN-13	3479775493800

CABS modules must be installed on CABS-APP Aluminium Profile.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved nVent, nVent CADDY, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

