

Rittal – The System.

Faster – better – everywhere.

► Kompaktni rasklopni ormari AE Oplemenjeni čelik – AE 1002.600

Date : 2018.12.07

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Kompaktni rasklopni ormari AE Oplemenjeni čelik – AE 1002.600

created: 07.12.2018 build on www.rittal.com/hr-hr



Product description

Material:	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Stainless steel 1.4301 (AISI 304) Lock insert: Die-cast zinc, nickel-plated
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
IK Code:	IK08
Supply includes:	Montažna ploča
Basic material:	Oplemenjeni čelik

Product features

Dimensions:	Width: 200 mm Height: 300 mm Depth: 155 mm
Mounting plate:	Width: 162 mm Height: 275 mm

Number of doors:	1
Lock version:	Cam
Number of locks:	1
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	4,1 kg
EAN:	4028177000056
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	AE Compact enclosure, WHD: 200x300x155 mm, Stainless steel 1.4301, with mounting plate, single-door, with one cam lock
Approvals	
Approvals:	CSA DNV-GL Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	EAC IK-Code Protection category
Declarations:	Declaration of conformity