

Rittal – The System.

Faster – better – everywhere.

 – **VX 8205.000**

Date : 2018.12.07

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



– VX 8205.000

created: 07.12.2018 build on www.rittal.com/hr-hr



Product description

Material:	Enclosure frame: Sheet steel, 1.5 mm Roof: Sheet steel, 1.5 mm Door: Sheet steel, 2.0 mm Rear panel: Sheet steel, 1.5 mm Gland plates: Sheet steel, 1.5 mm Mounting plate: Sheet steel 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK Code:	IK10
Supply includes:	Krovni lim Podni limovi Montažna ploča
Basic material:	Čelični lim

Product features

Dimensions:	Width: 1200 mm Height: 2000 mm Depth: 500 mm
--------------------	--

Mounting plate:	Width: 1099 mm Height: 1896 mm
Number of doors:	2
Packs of:	1 pc(s).
Weight/pack:	190,6 kg
EAN:	4028177813625
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	VX Baying enclosure system, WHD: 1200x2000x500 mm, sheet steel, with mounting plate, two doors at the front
Approvals	
Approvals:	CSA Lloyds Register of Shipping UL + C-UL
Certificates:	IK-Code
Declarations:	Declaration of conformity