

# Rittal – The System.

Faster – better – everywhere.

## ► Baying enclosure system VX25, stainless steel Basic enclosure – VX 8457.000

Date : Dec 17, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Baying enclosure system VX25, stainless steel Basic enclosure – VX 8457.000

created: 17.12.2019 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Material:**  
Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm  
Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed  
Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed  
Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed  
Gland plates: Stainless steel 1.4301 (AISI 304), 1.5 mm  
Mounting plate: Sheet steel, 3.0 mm

**Surface finish:**  
Enclosure frame and gland plates: Uncoated  
Door, roof and rear panel: Exterior brushed, grain size 400  
Mounting plate: Zinc-plated

**Protection category  
IP to IEC 60 529:** IP 55

**Protection category  
NEMA:** NEMA 12

**IK Code:** IK10

**Supply includes:**  
Enclosure frame  
Door(s)  
Door hinged on the right, may be swapped to the left  
Roof plate  
Gland plates  
Rear panel  
Mounting plate  
Lock: 3 mm double-bit  
2 punched rails 18 x 39 mm

**Note:** Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.

## Product features

**Dimensions:** Width: 600 mm  
Height: 1800 mm  
Depth: 500 mm

**Mounting plate:** Width: 499 mm  
Height: 1696 mm

**Number of doors:** 1

**Packs of:** 1 pc(s).

**Weight/pack:** 92.5 kg

**EAN:** 4028177920187

**Customs tariff number:** 94032080

**ETIM 7.0:** EC000261

**ETIM 6.0:** EC000261

**eCl@ss 8.0/8.1:** 27180101

**eCl@ss 6.0/6.1:** 27180101

**Product description:** VX Baying enclosure system, WHD: 600x1800x500 mm, stainless steel, 1.4301, with mounting plate, single door at the front

## Approvals

**Approvals:** CSA  
DNV-GL  
UL + C-UL

**Certificates:** EAC  
IK-Code

**Declarations:** Declaration of conformity