# Product data sheet Characteristics

## 16004

analog ammeter AMP - 1.3 In without dial - 72 x 72 mm



### Main

		۷.
Range	PowerLogic	
Device short name	AMP	
Product or component type	Ammeter	<u> </u>
Range compatibility	Prisma P door Prisma G door	i de constant de c
Technology type	Ferromagnetic	
Scale type	62 mm over 90°	
Mounting support	Front face	++

#### Complementary

o o i i pio i i o i i a i y		<u> </u>
Type of measurement	Current	- 6
Accuracy class	Class 1.5	
Power consumption in VA	1.1 VA	<u> </u>
Power consumption in VA	1.1 VA	E
Overload withstand	1.2 In, permanently 10 In, 5 s	ָּבֶּבֶּ קיני
Device mounting	Flush	
Operating position	30°/vertical	
Width	72 mm	<u>8</u>
Height	72 mm	
Depth	75 mm	<u> </u>
Temperature drift	+/- 0.003 %/°C	
		ū

#### Environment

Standards	IEC 60051-1	- d
	IEC 61000-4	pot
	IEC 61010-1	.sı
IP degree of protection	IP52	ntatic
Ambient air temperature for operation	-2550 °C	
Reference temperature	23 °C	— ob si
		ج —

#### Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

	Warranty	18 months
--	----------	-----------