

## Product data sheet

### Characteristics

## ZB4BD922

glava Ø22 + baza za montažu za  
potenciometar



### Main

|                               |                                        |
|-------------------------------|----------------------------------------|
| Range of product              | Harmony XB4                            |
| Product or component type     | Head + mounting base for potentiometer |
| Device short name             | ZB4                                    |
| Bezel material                | Chromium plated metal                  |
| Mounting diameter             | 22 mm                                  |
| Product compatibility         | For use with Ø 6.35 mm shaft           |
| Sale per indivisible quantity | 1                                      |
| Head type                     | Standard                               |

### Complementary

|                                    |                           |
|------------------------------------|---------------------------|
| Net weight                         | 0,08 kg                   |
| Resistance to high pressure washer | 7000000 Pa 55 °C 0.1 m    |
| Shape of signaling unit head       | Round                     |
| Operator profile                   | Knurled knob, with white) |
| Device presentation                | Basic element             |

### Environment

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                                      |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                             |
| Ambient air temperature for operation | -40...70 °C                                                                                                                             |
| Electrical shock protection class     | Class I IEC 60536                                                                                                                       |
| IP degree of protection               | IP66 IEC 60529                                                                                                                          |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                                      |
| IK degree of protection               | IK03 IEC 50102                                                                                                                          |
| Standards                             | EN/IEC 60947-5-4<br>UL 508<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-5<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>JIS C8201-1 |
| Product certifications                | DNV<br>CSA<br>RINA<br>LROS (Lloyds register of shipping)<br>GL<br>UL listed<br>BV                                                       |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                                           |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |

## Offer Sustainability

|                            |                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                   |
| Uredba REACH               | <a href="#">Izjava REACH</a>                                                                             |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Bez otrovnih teških metala | Da                                                                                                       |
| Bez žive                   | Da                                                                                                       |
| Informacije o RoHS izuzeću | <a href="#">Da</a>                                                                                       |
| Propis RoHS za Kinu        | <a href="#">Izjava RoHS Za Kinu</a>                                                                      |
| Izjava o očuvanju okoliša  | <a href="#">Ekološki Profil Proizvoda</a>                                                                |
| Profil cirkularnosti       | <a href="#">Informacije O Kraju Vijeka Trajanja</a>                                                      |

## Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|