



## Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2P + E
Device presentation	Complete product
Colour tint	White
Type of packing	Flow-pack

## Complementary

Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 2,5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13,0 mm
Material	ABS (acrylonitrile butadiene-styrene) cover frame ABS + PC central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...69 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	10 mm

Quantity per set	1
Net weight	0,08 kg

## Environment

Standards	IEC 60884-1
Product certifications	TSE VDE
IP degree of protection	IP20

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU RoHS	Sukladno <a href="#">Izjava EU RoHS</a>
Bez žive	Da
Informacije o RoHS izuzeću	<a href="#">Da</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS za Kinu</a> Proizvod izvan dosega propisa RoHS za Kinu. Informativna deklaracija o tvarima.
Izjava o očuvanju okoliša	<a href="#">Ekološki profil proizvoda</a>
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

## Contractual warranty

Jamstvo	18 months
---------	-----------