Product data sheet Characteristics

ETK30330

Ultra - minitrunking - 30 x 30 mm - PVC - white - 2 m





Main

Product or component type	Mini trunking
Colour tint	White RAL 9010
Quantity per set	88 m

Complementary

Trunking material	Plastic	<u> </u>
Compartment partitioning	1 compartment	(}
Trunking dimension	30 x 30 mm	
Fixing mode	Power cable : screw-fixed Pre-punched fixing hole with distance of 230 mm between centers	
Material	PVC (polyvinyl chloride)	9
Length	2000 mm	<u> </u>
Height	30 mm	<u></u>
Width	30 mm	
		<u> </u>

Environment

IP degree of protection	IP40	
IK degree of protection	IK07	<u>y</u> <u>v</u>
Ambient air temperature for operation	-560 °C	- 0
Environmental health and issues	Cadmium free Lead free	o propin
Product certifications	Low voltage directive 2006/95/EC	<u>9</u>
Standards	EN 50085-1 : 2005 EN 50085-2-1 : 2006	isting

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1826 - Schneider Electric declaration of conformity

Schneider Electric declaration of conformity

DEAGL		
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
·	Product Environmental Profile	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty		
Warranty period	18 months	