



Main

Range	TeSys
Product name	TeSys GV2
Device short name	GV2ME
Device application	Motor
Trip unit technology	Thermal-magnetic

Complementary

Poles description	3P
Network type	AC
Utilisation category	AC-3 IEC 60947-4-1 Category A IEC 60947-2
Network frequency	50 Hz
Fixing mode	35 mm symmetrical DIN rail clipped (Panel screwed with adaptor plate)
Operating position	Any position
Motor power kW	11 kW 400/415 V AC 50 Hz 15 kW 500 V AC 50 Hz
Breaking capacity	50 kA Icu 230/240 V AC 50 Hz IEC 60947-2 15 kA Icu 400/415 V AC 50 Hz IEC 60947-2 6 kA Icu 440 V AC 50 Hz IEC 60947-2 4 kA Icu 500 V AC 50 Hz IEC 60947-2 3 kA Icu 690 V AC 50 Hz IEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 % 230/240 V AC 50 Hz IEC 60947-2 40 % 400/415 V AC 50 Hz IEC 60947-2 50 % 440 V AC 50 Hz IEC 60947-2 75 % 500 V AC 50 Hz IEC 60947-2 75 % 690 V AC 50 Hz IEC 60947-2
Control type	Push-button
[In] rated current	25 A
Thermal protection adjustment range	20...25 A
Magnetic tripping current	327 A

[Ue] rated operational voltage	690 V AC 50 Hz IEC 60947-2
[Ui] rated insulation voltage	690 V AC 50 Hz IEC 60947-2
[Ith] conventional free air thermal current	25 A IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-2
Power dissipation per pole	2,5 W
Mechanical durability	100000 cycles
Electrical durability	100000 cycles AC-3 440 V
Maximum operating rate	25 cyc/h
Rated duty	Continuous IEC 60947-4-1
Connections - terminals	screw clamp terminals 2 1...6 mm ² solid screw clamp terminals 2 1,5...6 mm ² flexible without cable end screw clamp terminals 2 1...4 mm ² flexible with cable end
Tightening torque	1,7 N.m screw clamp terminals
Suitability for isolation	Yes IEC 60947-1
Phase failure sensitivity	Yes IEC 60947-4-1
Height	89 mm
Width	45 mm
Maksimalna dubina	78,5 mm
Net weight	0,26 kg

Environment

Standards	EN/IEC 60947-2 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	IECEE CB Scheme UL CSA CCC EAC ATEX
Protective treatment	TH
IP degree of protection	IP20 IEC 60529
IK degree of protection	IK04
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C IEC 60695-2-1
Operating altitude	2000 m

Broj pakirnih jedinica

Vrsta pakirne jedinice Paketa 1	PCE
Broj pakirnih jedinica u Paketu 1	1
Paket 1 Težina	286,75 g
Paket 1 Visina	4,8 cm
Paket 1 Širina	8,5 cm
Paket 1 Duljina	9,5 cm
Vrsta pakirne jedinice Paketa 2	S02
Broj pakirnih jedinica u Paketu 2	24
Paket 2 Težina	7,135 kg
Paket 2 Visina	15 cm
Paket 2 Širina	30 cm
Paket 2 Duljina	40 cm
Vrsta pakirne jedinice Paketa 3	P06
Broj pakirnih jedinica u Paketu 3	384

Paket 3 Težina	121,14 kg
Paket 3 Visina	75 cm
Paket 3 Širina	80 cm
Paket 3 Duljina	60 cm

Offer Sustainability

Štatus održive ponude	Proizvod Green Premium
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS za Kinu Proizvod izvan dosega propisa RoHS za Kinu. Informativna deklaracija o tvarima.
Izjava o očuvanju okoliša	Ekološki profil proizvoda

Contractual warranty

Jamstvo	18 months
---------	-----------