



Main

Range	Acti 9
Product or component type	Add-on residual current devices
Device short name	Vigi iC60
Poles description	4P
[In] rated current	40 A
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth leakage protection type	Type AC
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz EN 61009-1 400/415 V AC 50/60 Hz IEC 61009-1
Standards	EN 61009-1 IEC 61009-1
9 mm pitches	7

Complementary

Device location in system	Outgoer
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kVIEC 60947-2
Range compatibility	Acti 9 iC60 Acti 9 Reflex iC60
Product compatibility	Single terminal
Local signalling	Trip indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	By screws

Izjava: Ovi dokumenti ne mijenjaju ni su namijenjeni utvrđivanju primjerenosti ili pouzdanosti ovih proizvoda u specifičnim korisničkim primjenama.

Comb busbar and distribution block compatibility	Bottom YES
Height	91 mm
Width	135 mm
Depth	73,5 mm
Product weight	0,245 kg
Connections - terminals	Tunnel type terminal downside 1 1...35 mm ² rigid without cable end Tunnel type terminal downside 1 1...25 mm ² flexible without cable end Tunnel type terminal downside 1 1...25 mm ² flexible with cable end
Wire stripping length	14 mm bottom
Tightening torque	3,5 N.m bottom

Environment

IP degree of protection	IP20(IEC 60529 IP40 modular enclosure)IEC 60529
Pollution degree	3 IEC 60947-2
Electromagnetic compatibility	8/20 μs impulse withstand, 250 A IEC 61009-1
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
Direktiva EU RoHS	Pro-active compliance (Product out of EU RoHS legal scope) Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS za Kinu
Izjava o očuvanju okoliša	Ekološki profil proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------