# Podatkovna tablica proizvoda Značajke

# NSYSF20860P

Kućište Spacial SF s montažnom pločom sastavljeno – 2000 x 800 x 600 mm





#### Glavno

Glavilo	
Range	Spacial
Product name	Spacial SF
Device application	Multi-purpose
Product or component type	Suitable enclosure
Enclosure nominal height	2000 mm
Enclosure nominal width	800 mm
Enclosure nominal depth	600 mm
Enclosure mounting	Floor-standing
Device composition	1 door 1 mounting plate 1 rear panel 1 roof 1 structure 1 locking system with handle for door 2 sliding rails 4 mounting plate bracket

#### Complementary

Range	Spacial	
Product name	Spacial SF	
Device application	Multi-purpose	
Product or component type	Suitable enclosure	
Enclosure nominal height	2000 mm	
Enclosure nominal width	800 mm	
Enclosure nominal depth	600 mm	
Enclosure mounting	Floor-standing	
Device composition	1 door 1 mounting plate 1 rear panel 1 roof 1 structure 1 locking system with handle for door 2 sliding rails 4 mounting plate bracket	
	4 mounting plate bracket	
Complementary Structure type	Vertical uprights joined with top and bottom frames Panels and doors built into the structure	
	Vertical uprights joined with top and bottom frames	
Structure type	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm	
	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm Formed from a single section	
Structure type  Door type	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm Formed from a single section Plain on front	
Structure type  Door type  Number of doors	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm Formed from a single section Plain on front 1 on front	
Door type Number of doors Door opening side Lock type	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm Formed from a single section  Plain on front  1 on front  Reversible 120 °	
Door type Number of doors Door opening side	Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm Formed from a single section Plain on front 1 on front Reversible 120 ° 4 points lock, handle with 5 mm double bar insert on front door	

Removable parts	Rear panel fixed by screws
	Roof fixed by screws
	Door fixed by screws for hinge
	Mounting plate bracket fixed by screws
	Sliding rail fixed by screws
	Mounting plate fixed by screws for mounting plate bracket
Material	Galvanised steel for frame
	Galvanised steel for uprights
	Polyamide 6 with 30 % fibre glassfor handle
	Sheet steelfor door
	Sheet steel for panels
	Zamak for hinge
Surface finish	Epoxy-polyester powder
Colour	Enclosure: grey RAL 7035
	Handle: black RAL 9005

### Environment

Standards	IEC 62208
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	₫Utjecaj proizvoda na okoliš
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months