



Main

Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	German

Complementary

[In] rated current	10 A 16 A
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V
Plug, socket material	Housing self-extinguishing engineering polymer
Contacts material	Pins stainless steel Springs stainless steel
Cover type	Lid
Device mounting	Flush
Mounting mode	Panel-mounted
Connections - terminals	Captive screws
Location of conductor inlet	Side
Product weight	0,05 kg
Base dimension	65 x 85 mm
Height	85 mm
Width	65 mm
Depth	45,2 mm
Colour	Blue

Environment

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP54 IEC 60529

IK degree of protection	IK09 EN 62262
Fire resistance	850 °C IEC 60695-2-11
Relative humidity	50 % 40 °C 70 % 30 °C 90 % 20 °C
Ambient air temperature for operation	35 °C 86400 s) -25...40 °C

Offer Sustainability

Uredba REACH	 Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Pro-active compliance (Product out of EU RoHS legal scope)  Izjava EU RoHS
Bez otrovnih težkih metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	 Da
Propis RoHS za Kinu	 Izjava RoHS za Kinu

Contractual warranty

Jamstvo	18 months
---------	-----------