



Main

Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Panel-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing self-extinguishing engineering polymer
Contacts material	Sleeves brass
Connections - terminals	Captive screws
Cable cross section	2,5...10 mm ²
Product weight	0,2 kg
Base dimension	90 x 100 mm
Height	100 mm
Width	90 mm
Depth	117 mm
Colour	Grey RAL 7035)
Voltage colour	Blue

Environment

Standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 IEC 60529

IK degree of protection	IK08 EN 62262
Fire resistance	850 °C IEC 60695-2-1
Relative humidity	50 % 40 °C 70 % 30 °C 90 % 20 °C
Ambient air temperature for operation	35 °C 86400 s)

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	 Izjava REACH
Direktiva EU RoHS	Pro-active compliance (Product out of EU RoHS legal scope)  Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	 Da
Propis RoHS za Kinu	 Izjava RoHS za Kinu
Izjava o očuvanju okoliša	 Ekološki profil proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja

Contractual warranty

Jamstvo	18 months
---------	-----------