

Product data sheet

Characteristics

MGU3.775.18V

Unica – ravna lampica indikatora – 220 V AC –
1 m – zelena – bijela



Main

Range	Unica
Device application	Lighting
Product or component type	Flat indicator lamp
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
[Ue] rated operational voltage	220 V AC 50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	White

Complementary

Light block colour	Green
Bulb type	Neon lamp
Connections - terminals	Screw terminals
Cable cross section	2,5 Mm ² flexible 2,5 mm ² rigid
Material	ASA + PC mechanism cover
Standards	LV directive EMC directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	44 mm
Width	22,5 mm
Height	45 mm
Net weight	0,0645 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Petrol Ammonia Window-cleaning fluid Acetone Bleach UV resistant Alcohol Liquid soap
Environmental health and issues	Halogen free

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------