

### Pliers A cut above the rest for your health.

Wiha pliers combine high-quality materials with ergonomic comfort. Precise interaction between the joints and the exact workmanship of the blades and gripping surfaces ensure optimum functionality. Ergonomically designed and crafted to a high quality standard, they are comfortable to use, causing less body fatigue and thus making work more efficient.

The "OptiGrip" triple-point support design for combination and high-leverage combination pliers ensure an optimum, secure hold when handled. The circlip pliers from the Classic Series with their MagicTips<sup>®</sup> precision tips made of high-performance steel provide added safety and stability. With its angled plier shape, the Wiha Inomic<sup>®</sup> VDE product line is kind to the user's joints, muscles and tendons. Wiha also supplies suitable tools for stripping, skinning and crimping.



#### Application

#### Pliers

| For applications in electrics      | Installation pliers TriCut<br>Professional electric<br>Page 287                                  | <b>BiCut® Professional</b><br>electric high-<br>performance<br>diagonal cutters with<br>DynamicJoint®<br>Page 288 | Heavy-duty diagonal<br>cutters Professional<br>electric with<br>DynamicJoint®<br>Page 289        | Combination pliers<br>Professional electric<br>with DynamicJoint <sup>®</sup> and<br>OptiGrip<br>Page 290 |
|------------------------------------|--|---|--|---|
| 1 m                                |  |   |  |   |
|                                    | Needle nose pliers<br>Professional electric<br>Page 291  | Cable cutter<br>Professional electric<br>Page 293   | Water pump pliers<br>Professional electric,<br>with push button<br>adjustment<br>Page 293        |   |
| 1 August                           | $\prec \subset$  |   |  |   |
| Centre and a                       | Hacksaw electric<br>Page 295   | Stripping tool<br>automatic<br>Page 295   | <b>Stripping tool</b><br>Page 296  | Automatic crimp tool,<br>for wire-end sleeves<br>hex crimping<br>Page 298                                 |
| 1 81                               |  |   |  |   |
|                                    |  |   |  |   |
| For applications in mechanics      | Professional BiCut®<br>high-performance<br>diagonal cutters<br>with DynamicJoint®,<br>Switchable | Heavy-duty diagonal<br>cutters Professional with<br>DynamicJoint <sup>®</sup><br>Page 303                         | Combination pliers<br>Professional with<br>DynamicJoint <sup>®</sup> and<br>OptiGrip<br>Page 304 | <b>Needle-nose pliers<br/>Professional</b><br>Page 306  |
| A CONTRACTOR                       | Page 301   |   |  | ~~  |
|                                    | Plastic diagonal cutters<br>Classic, with opening<br>spring without bevelled<br>edge<br>Page 307 | Pliers wrench Classic<br>Page 308   | Water pump pliers<br>QuickFix Professional<br>automatic<br>Page 310                              | Classic circlip pliers<br>with MagicTips®,<br>straight<br>Page 312  |
|                                    |  |   | 055  |   |
| For applications<br>in electronics | Pliers set Professional<br>ESD<br>Page 316   | Needle nose pliers<br>Professional ESD<br>Page 319  | <b>Universal tweezers</b><br><b>Professional ESD</b><br>Page 320                                 | Needle nose pliers<br>Electronic<br>Page 323  |
|                                    | AV AV  |   | and a second   |   |

Tools that work for you

#### Pliers set Professional electric

#### Pliers set Industrial electric



|          | nation pliers, needle nose pliers, diagonal<br>s 3-pcs.  | Z 99 0 001 06     |
|----------|--|-------------------|
| Order-N  | No.  |                   |
| 26852    |  | 1                 |
| Trimm    | ing / cutting  |                   |
| X        | Professional electric diagonal cutters with Dynam 1/2" (43335)   | nicJoint® 160 x 6 |
| Supply   | ring / holding   |                   |
|          | Combination pliers Professional electric with Dyn<br>OptiGrip with extra long cutting edge, VDE and G<br>180mm, 7" (26708) |                   |
| •        | Needle nose pliers Professional electric with cutti<br>shape, VDE and GS tested / 200mm, 8" (2672                          | 0 0 0             |
| Manufact | tured acc. to IEC 60900.   |                   |

| Combinat  | tion pliers, needle nose pliers,                               | Perfect<br>20%<br>Power<br>diagonal | Z 99 0 001 09 |
|-----------|--|-------------------------------------|---------------|
| Order-No. |  |                                     |               |
| 38637     |  | 1                                   |               |
| Trimming  | / cutting  |                                     |               |
| X         | Industrial electric diagonal cutters v<br>160 x 6 1/2" (43336) | with DynamicJoin                    | t®            |
| Supplying | ı / holding  |                                     |               |
|           |  |                                     |               |

| oupprying / noraling  |       |
|---|-------|
| Industrial electric combination pliers with Dyn<br>OptiGrip with extra long cutting edge, VDE ar<br>180mm, 7" (33186) |       |
| <ul> <li>Industrial electric needle nose pliers with cutt<br/>shape, VDE and GS tested / 200mm, 8" (3)</li> </ul>     | 0 0 0 |
| Manufactured acc. to IEC 60000  |       |





## 286 **wiha** 🗠



|                                 |     |          |    |     |    | Z 14 1 06 |  |
|---------------------------------|-----|----------|----|-----|----|-----------|--|
| Order-No.                       | ₩mm | <b>↓</b> | ≫  | Ømm | SB | Ĺ         |  |
| 38552                           | 170 | 7        | 13 | 1.6 |    | 5         |  |
| 38853                           | 170 | 7        | 13 | 1.6 | х  | 5         |  |
| Manufactured acc. to IEC 60900. |     |          |    |     |    |           |  |

|           |     |   |    |     |    | Z 14 1 01 |
|-----------|-----|---|----|-----|----|-----------|
| Order-No. | ₩mm | ₩ | ≫  | Ømm | SB |           |
| 38627     | 170 | 7 | 13 | 1.6 |    | 5         |
| 38854     | 170 | 7 | 13 | 1.6 | х  | 5         |
|           |     |   |    |     |    |           |

### INFOBOX: VDE-certified tools

DE CS 21000 V A1000 V





Wiha VDE-tested tools are subject to stringent safety test procedures.

All tools with the special marking have been tested at 10,000 V AC and are therefore approved for use at 1,000 V AC and 1,500 V DC.

The following equipment is required for all work on or around live components and should be appropriate for the specific task

- insulating personal protective equipment
- insulating safety mechanisms
- insulated tools

Before starting work, you must disconnect all active, live components of electrical machines and equipment and ensure that they remain disconnected while you carry out the work.

This is achieved by complying with the five safety rules:

- disconnect
- secure against reconnection
- ensure power is switched off
- earth and short-circuit
- cover or block off adjacent live components

Certified by the VDE Testing and Certification Institute and individually tested according to the international standard IEC 60900.



Stripping diagonal cutters Professional electric with DynamicJoint®

Professional electric diagonal cutters with DynamicJoint®





A1000 V

Z 12 1 06

|   |     |          |    |     |    | Z 14 0 06 |  |
|---|-----|----------|----|-----|----|-----------|--|
| Order-No.                                     | ₩mm | <b>↓</b> | ≫  | Ømm | SB | É         |  |
| 26745   | 160 | 6 ½      | 13 | 1.6 |    | 5         |  |
| 27431   | 160 | 6 ½      | 13 | 1.6 | х  | 5         |  |
| DIN ISO 5749. Manufactured acc. to IEC 60900. |     |          |    |     |    |           |  |

| Order-No.    | ₩mm | <b>↓</b> | >< | Ømm | SB |   |  |
|--------------|-----|----------|----|-----|----|---|--|
| 43326        | 140 | 5 1/2"   | 16 | 1,6 |    | 5 |  |
| 43453        | 140 | 5 1/2"   | 16 | 1,6 | х  | 5 |  |
| 43335        | 160 | 6 1/2"   | 17 | 2   |    | 5 |  |
| 43458        | 160 | 6 1/2"   | 17 | 2   | х  | 5 |  |
| 43340        | 180 | 7"       | 18 | 2,3 |    | 5 |  |
| 43463        | 180 | 7"       | 18 | 2,8 | х  | 5 |  |
| Manufactured |     | C 60900. |    |     |    |   |  |

Manufactured acc. to IEC 60900.

BiCut<sup>®</sup> Professional electric high-performance diagonal cutters with DynamicJoint<sup>®</sup> X :h0 

Industrial electric diagonal cutters with DynamicJoint®



| Ð                                    |    |
|--------------------------------------|----|
| red <mark>dot</mark> award<br>winner | 20 |

| Switchable                      | е   | Z 18 0 06 |    |     |    |   |  |
|---------------------------------|-----|-----------|----|-----|----|---|--|
| Order-No.                       |     | <b>₩</b>  | ≫  | Ømm | SB | É |  |
| 38191                           | 200 | 8         | 21 | 3   |    | 5 |  |
| 38984                           | 200 | 8         | 21 | 3   | х  | 5 |  |
| Manufactured acc. to IEC 60900. |     |           |    |     |    |   |  |

|           |     |          |    |     |    | Z12109 |
|-----------|-----|----------|----|-----|----|--------|
| Order-No. | ₩mm | <b>↓</b> | ≫  | Ømm | SB | í 🖬    |
| 43327     | 140 | 5 1/2"   | 16 | 1,6 |    | 5      |
| 43454     | 140 | 5 1/2"   | 16 | 1,6 | Х  | 5      |
| 43336     | 160 | 6 1/2"   | 17 | 2   |    | 5      |
| 43459     | 160 | 6 1/2"   | 17 | 2   | х  | 5      |
| 43341     | 180 | 6"       | 18 | 2,8 |    | 5      |
| 43464     | 180 | 7"       | 18 | 2,8 | х  | 5      |

Manufactured acc. to IEC 60900.



## Heavy-duty diagonal cutters Professional electric with $\mbox{DynamicJoint}^{\odot}$

# willing wetre

Industrial electric heavy-duty diagonal cutters with DynamicJoint®



| with switc                                    | hable | Z 16 3 06 |    |     |    |   |  |
|---|-------|-----------|----|-----|----|---|--|
| Order-No.                                     | ₩mm   | ₩         | >< | Ømm | SB |   |  |
| 40921   | 160   | 6,5       | 17 | 2   |    | 5 |  |
| 41309   | 160   | 6,5       | 17 | 2   | х  | 5 |  |
| 41274   | 180   | 7         | 18 | 2,3 |    | 5 |  |
| 41319   | 180   | 7         | 18 | 2,3 | х  | 5 |  |
| 41279   | 200   | 8         | 19 | 2,5 |    | 5 |  |
| 41329   | 200   | 8         |    | 2,5 | x  | 5 |  |
| DIN ISO 5749. Manufactured acc. to IEC 60900. |       |           |    |     |    |   |  |

| with switc   | hable | Z 16 3 09 |    |     |    |          |
|--------------|-------|-----------|----|-----|----|----------|
| Order-No.    | ₩mm   | <b>↓</b>  | ≫  | Ømm | SB | <u>ن</u> |
| 40922        | 160   | 6,5       | 17 | 2   |    | 5        |
| 41310        | 160   | 6,5       | 17 | 2   | х  | 5        |
| 41275        | 180   | 7         | 18 | 2,3 |    | 5        |
| 41320        | 180   | 7         | 18 | 2,3 | х  | 5        |
| 41280        | 200   | 8         | 19 | 2,5 |    | 5        |
| 41330        | 200   | 8         | 19 | 2,5 | х  | 5        |
| DIN ISO 5749 |       |           |    |     |    |          |

### INFOBOX: DynamicJoint®





## Wiha DynamicJoint $^{\ensuremath{\$}}$ – A new dimension in strength and durability

- Innovative: Optimised joint construction.
- Effective: Minimal power loss means less force needed for cutting.
- Permanent: Optimal performance even after thousands of cuts.

#### INFOBOX: Heavy-duty diagonal cutters





### with switchable opening spring

- Up to 40% more cutting force thanks to optimised leverage.
- Opening spring with on/off function for fatigue-free work.
- Opening spring can be activated with just one hand.



High-leverage combination pliers Professional electric with DynamicJoint<sup>®</sup> and OptiGrip





#### with extra long cutting edge

| with extra   | long o | cutting  |    | Z 01 0 06 |        |   |
|--------------|--------|----------|----|-----------|--------|---|
| Order-No.    | ₩mm    | <b>↔</b> | >  | Ømm       | SB     |   |
| 26705        | 160    | 6 ½      | 15 | 1.6       |        | 5 |
| 27328        | 160    | 6 ½      | 15 | 1.6       | х      | 5 |
| 26708        | 180    | 7        | 16 | 1.8       |        | 5 |
| 27418        | 180    | 7        | 16 | 1.8       | х      | 5 |
| 26711        | 200    | 8        | 17 | 2         |        | 5 |
| 27419        | 200    | 8        | 17 | 2         | х      | 5 |
| DIN ISO 5746 |        |          |    |           | ****** |   |



Z 02 0 06

#### with extra long cutting edge

|     | 8 🔨                      | Ømm   | [SB]]   |  |
|-----|--------------------------|---|---|--|
| ) 8 | 18                       | 2.3   |   | 5  |
| ) 8 | 18                       | 2.3   | х   | 5  |
| 5 9 | 19                       | 2.5   |   | 5  |
| 5 9 | 19                       | 2.5   | х   | 5  |
|     | ) 8<br>) 8<br>5 9<br>5 9 | 0     8     18       0     8     18       5     9     19       5     9     19 | 0         8         18         2.3           0         8         18         2.3           5         9         19         2.5           5         9         19         2.5 | 0     8     18     2.3     x       5     9     19     2.5       5     9     19     2.5 |

DIN ISO 5746. Manufactured acc. to IEC 60900

Industrial electric combination pliers with DynamicJoint® and OptiGrip



#### with extra long cutting edge Z 01 0 09 ≫ Order-No. Ømm SB mm **`**\_\_' 33186 5 180 7 16 1.8 38855 180 7 5 16 1.8 Х

DIN ISO 5746. Manufactured acc. to IEC 60900.

High-leverage industrial electric combination pliers with DynamicJoint<sup>®</sup> and OptiGrip





|              |        |             |    |     |    | Z 02 0 09 |
|--------------|--------|-------------|----|-----|----|-----------|
| Order-No.    | ₩mm    | <b>↓</b>    | ≫  | Ømm | SB | <b>L</b>  |
| 35465        | 225    | 9           | 19 | 2.5 |    | 5         |
| 38856        | 225    | 9           | 19 | 2.5 | х  | 5         |
| DINLICO ETAC | Manufa | ature al ar |    |     |    |           |

DIN ISO 5746. Manufactured acc. to IEC 60900.



#### Industrial lineman's pliers with DynamicJoint®



| with extra | -   | Z 02 2 02 |    |     |    |   |
|------------|-----|-----------|----|-----|----|---|
| Order-No.  | ₩mm | <b>↓</b>  | ≫  | Ømm | SB |   |
| 40927      | 250 | 10        | 20 | 2.5 |    | 5 |





#### with cutting edge straight shape

| with cuttir | ıg edg  | e stra   |    | Z 05 0 06 |    |   |  |  |  |  |  |
|-------------|---|----------|----|-----------|----|---|--|--|--|--|--|
| Order-No.   | ₩mm   | <b>↓</b> | ≫  | Ømm       | SB |   |  |  |  |  |  |
| 26720       | 160   | 6 ½      | 16 | 1.2       |    | 5 |  |  |  |  |  |
| 27422       | 160   | 6 ½      | 16 | 1.2       | х  | 5 |  |  |  |  |  |
| 26727       | 200   | 8        | 17 | 1.6       |    | 5 |  |  |  |  |  |
| 27423       | 200   | 8        | 17 | 1.6       | х  | 5 |  |  |  |  |  |
|             | DIN ISO 5745. Manufactured acc. to IEC 60900. |          |    |           |    |   |  |  |  |  |  |

#### Industrial electric needle nose pliers



#### with cutting edge straight shape

|               |        | ↔          |           | ~      | SB |   |
|---------------|--------|------------|-----------|--------|----|---|
| 35477         |        | 6 1/2      |           | 1.2    |    | 5 |
| 38857         |        | 6 1/2      |           |        | х  | 5 |
| 33178         | 200    | 8          | 17        | 1.6    |    | 5 |
| 38858         | 200    | 8          | 17        | 1.6    | х  | 1 |
| DIN ISO 5745. | Manufa | actured ac | c. to IFC | 60900. |    |   |

#### Classic lineman's pliers with DynamicJoint®



Ømm SB

Х

2.5

2.5

>

20

20

INFOBOX: **OptiGrip** 

with extra long cutting edge

₩mm

250

250

**1** 

10

10

Order-No.

40709

41218



5

5



#### Wiha OptiGrip - optimal grip due to newly designed gripping surfaces

- A firm hold: The "triple-point support" protects the workpiece from twisting or slipping.
- Highly effective: Optimum grip even with large jaw opening - and at the same time significantly less force needed.
- A wide selection: Now in standard Wiha combination pliers and high leverage combination pliers.

Z 05 0 09



#### Needle nose pliers Professional electric

#### with cutting edge curved shape, approx. 40°

| Order-No. | mm  | <b>↓</b> II | ≫  | Ømm | SB |   |
|-----------|-----|-------------|----|-----|----|---|
| 26728     | 160 | 6 ½         | 16 | 1.2 |    | 5 |
| 27424     | 160 | 6 ½         | 16 | 1.2 | х  | 5 |
| 26729     | 200 | 8           | 17 | 1.6 |    | 5 |
| 27425     | 200 | 8           | 17 | 1.6 | х  | 5 |

DIN ISO 5745. Manufactured acc. to IEC 60900.



## with cutting edge curved shape, approx. $40^\circ$

| Order-No.                                     | ₩mm | <b>↓</b> | ≫  | Ømm | SB | <b>H</b> |  |  |  |
|---|-----|----------|----|-----|----|----------|--|--|--|
| 35462   | 200 | 8        | 17 | 1.6 |    | 5        |  |  |  |
| 38859   | 200 | 8        | 17 | 1.6 | х  | 5        |  |  |  |
| DIN ISO 5745. Manufactured acc. to IEC 60900. |     |          |    |     |    |          |  |  |  |

Long round-nose pliers Professional electric



|           |     |          |    | Z 09 0 06 |
|-----------|-----|----------|----|-----------|
| Order-No. | ⁺mm | <b>↔</b> | SB | <b></b>   |
| 26735     | 160 | 6 ½      |    | 5         |
| 27427     | 160 | 6 ½      | Х  | 5         |

DIN ISO 5745. Manufactured acc. to IEC 60900.





DIN ISO 5745. Manufactured acc. to IEC 60900.

Z 05 1 06

GS

Z 05 1 09

Long flat-nose pliers Professional electric



#### Cable cutter Professional electric





DYE CS 1000 V 1000 V 160 60900

|              |     |          |    |     |    | Z 50 1 06 |
|--------------|-----|----------|----|-----|----|-----------|
| Order-No.    | ₩mm | <b>↓</b> | ≫  | mm² | SB |           |
| 34743        | 160 | 6 ½      | 16 | 50  |    | 5         |
| 35704        | 160 | 6 ½      | 16 | 50  | х  | 5         |
| 34744        | 200 | 8        | 20 | 60  |    | 5         |
| 35705        | 200 | 8        | 20 | 60  | х  | 5         |
| Manufactured |     |          |    |     |    |           |



#### Water pump pliers Professional electric

Cable cutter Classic





| вох туре      |     | Z 21 0 06 |    |    |    |   |
|---------------|-----|-----------|----|----|----|---|
| Order-No.     | ₩mm | ₩         | 0; | 0: | SB |   |
| 33520         | 250 | 10        | 2  | 50 |    | 5 |
| 38631         | 250 | 10        | 2  | 50 | х  | 5 |
| DIN ISO 8976. |     | ctured ac |    |    |    |   |

## Water pump pliers Professional electric



A1000 V AIEC 60900

| with | push | button | adjustment |
|------|------|--------|------------|
| with | push | button | adjustment |

| with push     | buttor |           | Z 22 0 06 |        |           |          |
|---------------|--------|-----------|-----------|--------|-----------|----------|
| Order-No.     | ₩mm    | ₩         | 0;        | 0:     | <b>SB</b> | <u>ل</u> |
| 37450         | 250    | 10        | 2         | 50     |           | 5        |
| 38632         | 250    | 10        | 2         | 50     | Х         | 5        |
| DIN ISO 8976. | Manufa | ctured ac | c. to IEC | 60900. |           |          |

DEG A1000 V JEC 60900

Z 50 1 09

| Order-No.    | ₩mm | <b>↓</b> | ≫  | mm² | SB | É |
|--------------|-----|----------|----|-----|----|---|
| 38636        | 160 | 6 ½      | 16 | 50  |    | 5 |
| 38865        | 160 | 6 ½      | 16 | 50  | х  | 5 |
| 35479        | 200 | 8        | 20 | 60  |    | 5 |
| 38866        | 200 | 8        | 20 | 60  | х  | 5 |
| Manufactured |     |          |    |     |    |   |



#### Stripping pliers Professional electric

 $\bullet$ 

Order-No.

36711

38867

#### Z 55 0 06 ₩m SB D Order-No. **↔** mm² Ø 26847 5 160 6 1⁄2 5 10 27437 160 6 ½ 5 10 5 Х DIN ISO 5743. Manufactured acc. to IEC 60900.

#### Industrial electric stripping pliers

DIN ISO 5743. Manufactured acc. to IEC 60900.

Stripping pliers Professional

160 6 1/2

₩mm

160

**₩** 

6 1/2

Ø

5

5

SB

Х

mm²

10

10

## 

 $\mathbb{W}$ 

|               |   |          |   |     |    | Z 55 0 05 |
|---------------|---|----------|---|-----|----|-----------|
| Order-No.     | ⁺mm                                     | <b>↓</b> | Ø | mm² | SB |           |
| 26846         | 160                                     | 6 ½      | 5 | 10  |    | 5         |
| DIN ISO 5743. | ••••••••••••••••••••••••••••••••••••••• | *******  |   |     |    |           |

#### 160 6 ½ 5 10 34313 160 6 ½ 5 10 5 х DIN ISO 5743.

#### Stripping pliers Classic

B

WW

 $\mathbb{W}$ 

5

5

A1000 V

Z 55 0 09

Stripping pliers Industrial



|               |     |        |   |                 |    | 2 55 0 01 |
|---------------|-----|--------|---|-----------------|----|-----------|
| Order-No.     | mm  | ₩      | Ø | mm <sup>2</sup> | SB | í 🖬       |
| 26845         | 160 | 6 ½    | 5 | 10              |    | 5         |
| 27368         | 160 | 6 ½    | 5 | 10              | х  | 5         |
| DIN ISO 5743. |     | •••••• |   | ••••••          |    |           |

Z 55 0 02 Order-No. **₩** SB D mm Ø  $mm^2$ 5 32345

| • |       |  |
|---|-------|--|
|   | 2     |  |
|   | witho |  |
|   |       |  |



#### Stripping tool automatic

Stripping tool automatic





| up to 16 mm <sup>2</sup> in blister pack ZS |     |          |           |      |    |   |  |
|---|-----|----------|-----------|------|----|---|--|
| Order-No.                                   | ₩mm | <b>↔</b> | mm²       | AWG  | SB |   |  |
| 42062                                       | 200 | 8        | 0,03 - 16 | 32-5 | Х  | 1 |  |

| up to 6 mm <sup>2</sup> in blister pack |  |
|---|--|
|---|--|

Hacksaw electric

ι

| up to 6 mm | ir D |     | 24675   |       |    |   |
|------------|------|-----|---------|-------|----|---|
| Order-No.  | €mm  | ₩   | mm²     | AWG   | SB |   |
| 36050      | 190  | 7 ½ | 0,2-6,0 | 24-10 | х  | 1 |

wihae

#### Spare blade and gripping jaw set



#### for automatic stripping tool

| for automatic stripping tool | Z 57 0 001 06K |
|------------------------------|----------------|
| Order-No.                    |                |
| 42162                        | 1              |

#### INFOBOX:

#### Stripping tool, automatic up to 16mm<sup>2</sup>





- These pliers can handle a wide range of cables, thus combining two pairs of pliers in one.
- The supplied damper can be used to lessen recoil caused by larger cable gauges, such as those greater than 6 mm<sup>2</sup>, thus helping to protect wrists.
- Precise cutting to length thanks to adjustable longitudinal stop.
- Integrated hand protection along the cutting edge guards against injury.

| insulated with three saw blades 150 mm |                |     |    |   |  |  |  |
|--|----------------|-----|----|---|--|--|--|
| Order-No.                              | <del>~~~</del> | ₩mm | SB |   |  |  |  |
| 43125                                  | 150            | 280 | х  | 1 |  |  |  |

#### insulated with three saw blades 150 mm

| Order-No. |     | ₩mm | SB ) |   |
|-----------|-----|-----|------|---|
| 43125     | 150 | 280 | х    | 1 |



#### Stripping tool



| with self-rotating trailing blade 24 |     |          |        |    |   |  |  |
|--------------------------------------|-----|----------|--------|----|---|--|--|
| Order-No.                            | ₩mm | <b>↔</b> | Ømm    | SB |   |  |  |
| 35969                                | 165 | 6½       | 4,0-28 |    | 1 |  |  |
| 35538                                | 165 | 6½       | 4,0-28 | х  | 1 |  |  |

## and the 18

| for coaxial cable, in blister pack 24 |     |    |         |           |          |  |  |
|---------------------------------------|-----|----|---------|-----------|----------|--|--|
| Order-No.                             | ₩mm | ₩  | mm²     | <b>SB</b> | <u>í</u> |  |  |
| 36051                                 | 110 | 4¼ | 4,8-7,5 | x         | 1        |  |  |

#### Cable stripping knife



#### straight cutting edge for round cables in blister pack

| Order-No.    | ₩mm        | <b>→</b> | SB |
|--------------|------------|----------|----|
| 38798        | 200        | 8        | х  |
| Manufactured | acc. to IE | C 6090   | Э. |



#### for round cable, in blister pack

Stripping tool

Stripping tool

24680

☆1000 V JEC 60900

24678

| for round c | ,   | 24677 |      |    |   |
|-------------|-----|-------|------|----|---|
| Order-No.   | ₩mm | ₩     | mm²  | SB |   |
| 36052       | 125 | 5     | 8-13 | х  | 1 |

#### Cable stripping knife



hooked blade with sliding shoe for round cable, in blister pack

| Order-No. | ₩mm | € | SB |   |
|-----------|-----|---|----|---|
| 36053     | 200 | 8 | х  | 1 |

Manufactured acc. to IEC 60900.





#### Crimping pliers Classic



mm²

0,25-2,5

5

#### Crimping pliers Professional electric



| Z 60 0 01 |              |     |           |          |    | Z 60 0 06 |
|-----------|--------------|-----|-----------|----------|----|-----------|
| ••••••    | Order-No.    | mm  | €<br>II   | mm²      | SB |           |
|           | 35861        | 145 | 5 3⁄4     | 0,25-2,5 |    | 5         |
| ••••••    | 38985        |     | 5 3⁄4     | 0,25-2,5 | x  | 5         |
|           | DIN ISO 5743 |     | ctured ac |          |    |           |

Crimping pliers Professional electric



|               |        |           |                  |    | Z 60 0 06 |
|---------------|--------|-----------|------------------|----|-----------|
| Order-No.     | ₩mm    | ₩         | mm²              | SB |           |
| 35862         | 180    | 7         | 0,25-16          |    | 5         |
| 38986         | 180    | 7         | 0,25-16          | x  | 5         |
| DIN ISO 5743. | Manufa | ctured ac | c. to IEC 60900. |    |           |

Crimping pliers Classic

Order-No. mm II

145 534

28330

DIN ISO 5743.



|               |   |          |         | Z 60 0 01 |
|---------------|---|----------|---------|-----------|
| Order-No.     | ⁺mm                                     | <b>↓</b> | mm²     |           |
| 30066         | 180                                     | 7        | 0,25-16 | 5         |
| DIN ISO 5743. | ••••••••••••••••••••••••••••••••••••••• |          | ••••••  |           |

