

Product data sheet

Characteristics

MGU3.109T.18

Unica – ozibna sklopka – 10 AX, 250 V AC – 1 m – bijela



Main

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Switch function	Double 2-way
Switch application	Roller blind
Rated current	10 AX 250 V AC 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	White

Complementary

Contacts type and composition	1 C/O + 1 C/O
Mechanical interlocking	Interlock between up/down
[Iu] rated interrupted current	2,5 A motor
Opening distance	> 3 mm
Marking	UP Down
Connections - terminals	Screw terminals
Cable cross section	2,5 Mm ² flexible 2,5 mm ² rigid
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _{un} , cos phi = 0,3
Electrical durability	10000 cycles, cos phi = 0,6
Insulation resistance	> 5 MOhm 500 V
Dielectric strength	2000 V
Material	ASA + PC mechanism cover
Standards	LV directive EN 60669-1 EMC directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	21 mm
Depth	33 mm
Width	22,4 mm
Height	45 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Petrol Alcohol UV resistant Bleach Ammonia Oil Liquid soap Acetone
Environmental health and issues	Halogen free

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------