

Product data sheet

Characteristics

MGU3.161.18S

Unica – ozibna sklopka – 1–smjerno – 16 AX
250 V AC – 1 m – bijela



Main

Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Switch
Device presentation	Mechanism
Switch function	1-pole 1-way
Device application	Control
Colour tint	White

Complementary

Rated current	16 AX 250 V AC 50/60 Hz
Electrical durability	5000 cycles
Insulation resistance	> 5 MOhm 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0,3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	1 module
Pilot light	LED amber 0.15 mA 15 °C
Connections - terminals	Screw terminals
Cable cross section	0...4 Mm ² rigid 0...4 mm ² flexible
Material	ASA + PC mechanism cover
Fixing mode	Clip-in
Width	22,5 mm
Height	45 mm
Depth	33 mm
Embedding depth	21 mm
Net weight	0,0239 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EN 60669-1 EMC directive LV directive

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. This information is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Bleach Liquid soap Petrol Alcohol Acetone Window-cleaning fluid Ammonia Oil UV resistant
Environmental health and issues	Halogen free

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACh	Izjava REACh
REACh, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------