

Product data sheet

Characteristics

MGU3.775.18T

Unica – ravna lampica indikatora – 220 V AC –
1 m – bijela



Main

Range	Unica
Device application	Lighting
Product or component type	Flat indicator lamp
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
[Ue] rated operational voltage	220 V AC 50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	White

Complementary

Light block colour	Transparent
Bulb type	Neon lamp
Connections - terminals	Screw terminals
Cable cross section	2,5 Mm ² flexible 2,5 mm ² rigid
Material	ASA + PC mechanism cover
Standards	EMC directive LV directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	44 mm
Width	22,5 mm
Height	45 mm
Net weight	0,0645 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Petrol Acetone Ammonia UV resistant Bleach Alcohol Window-cleaning fluid Oil Liquid soap
Environmental health and issues	Halogen free

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.

Contractual warranty

Jamstvo	18 months
---------	-----------