



### Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 1 1,5 VA Class 3 2,5 VA
[In] rated current	75 A

### Complementary

Current transformer type	Tropicalised for cable
Current transformer ratio	75/5
[I <sub>th</sub> ] conventional free air thermal current	4,5 kA
Dynamic withstand current	2.5 I <sub>th</sub>
Maximum safety factor	5
[U <sub>e</sub> ] rated operational voltage	< 720 V AC 50/60 Hz
[U <sub>i</sub> ] rated insulation voltage	3 kV
Mounting mode	Clip-on By screws
Mounting support	DIN rail Mounting plate
Width	Outside 44 mm
Height	Outside 65 mm
Depth	Frame 30 mm Total 37 mm
Diameter	21 mm
Net weight	0,19 kg
[U <sub>imp</sub> ] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B

Cable outer diameter	21 mm
Sealing	With

## Environment

Standards	IEC 61869-2 VDE 0414
Product certifications	CE EAC
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno <a href="#">Izjava EU RoHS</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS za Kinu</a> Proizvod izvan dosega propisa RoHS za Kinu. Informativna deklaracija o tvarima.
Izjava o očuvanju okoliša	<a href="#">Ekološki profil proizvoda</a>
Profil cirkularnosti	<a href="#">Informacije o kraju vijeka trajanja</a>
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.