



## Main

Range	PratiKa
Product or component type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

## Complementary

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing self-extinguishing engineering polymer
Contacts material	Sleeves brass
Connections - terminals	Captive screws
Cable cross section	1...4 mm <sup>2</sup>
Cable outer diameter	8...15 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 16
Product weight	0,144 kg
Height	129 mm
Width	73 mm
Depth	73 mm
Colour	Grey RAL 7035)
Voltage colour	Blue

## Environment

Standards	IEC 60309-2
-----------	-------------

IEC 60309-1

IP degree of protection	IP67 IEC 60529
IK degree of protection	IK08 EN 62262
Fire resistance	850 °C IEC 60695-2-11
Relative humidity	50 % 40 °C 70 % 30 °C 90 % 20 °C
Operating altitude	2000 m
Ambient air temperature for operation	35 °C 86400 s ) -25...40 °C

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	 <a href="#">Izjava REACH</a>
Direktiva EU RoHS	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">Izjava EU RoHS</a>
Bez žive	Da
Informacije o RoHS izuzeću	 <a href="#">Da</a>
Propis RoHS za Kinu	 <a href="#">Izjava RoHS za Kinu</a>
Izjava o očuvanju okoliša	 <a href="#">Ekološki profil proizvoda</a>
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja

## Contractual warranty

Jamstvo	18 months
---------	-----------