



3 372 54



3 372 64



3 372 74



3 372 84



0 203 99

Pack	Cat.Nos	Metal doors
		Supplied with handle Cat.No 3 397 10
		<b>For cabinets with 24 modules per row</b>
		For cabinet (no. of modules)
1	3 372 52	2 x 24
1	3 372 53	3 x 24
1	3 372 54	4 x 24
1	3 372 55	5 x 24
1	3 372 56	6 x 24
1	3 372 57	7 x 24
1	3 372 58	8 x 24
		<b>For cabinets with 36 modules per row</b>
1	3 372 64	4 x 36
1	3 372 65	5 x 36
1	3 372 66	6 x 36
1	3 372 67	7 x 36
1	3 372 68	8 x 36
		<b>Glass doors</b>
		<b>For cabinets with 24 modules per row</b>
		For cabinet (no. of modules)
1	3 372 72	2 x 24
1	3 372 73	3 x 24
1	3 372 74	4 x 24
1	3 372 75	5 x 24
1	3 372 76	6 x 24
1	3 372 77	7 x 24
1	3 372 78	8 x 24
		<b>For cabinets with 36 modules per row</b>
1	3 372 84	4 x 36
1	3 372 85	5 x 36
1	3 372 86	6 x 36
1	3 372 87	7 x 36
1	3 372 88	8 x 36
		<b>Replacement handle for doors</b>
1	3 397 10	Handle for XL <sup>3</sup> S 160 door
1	3 397 15	Locking handle no. 405 Supplied with a set of 2 keys
		<b>Accessories</b>
1	3 374 04	<b>Joining kit</b> For connecting two XL <sup>3</sup> S 160 cabinets vertically
1	3 374 00	<b>Wall mounting lugs</b> Set of 4 lugs for wall mounting
1	3 374 06	<b>Fixing kit for hollow partition</b> Kit for fixing XL <sup>3</sup> -S 160 flush-mounting cabinets in hollow partitions
1	3 374 05	<b>Fixing supports for ducting</b> Set of 2 supports
		<b>Fixing plate and faceplate for DPX<sup>3</sup> 160</b>
1	3 374 10	For XL <sup>3</sup> S 160 cabinets with 24 modules per row
1	3 374 11	For XL <sup>3</sup> S 160 cabinets with 36 modules per row

Pack	Cat.Nos	Self-adhesive document holders for plans
		<b>Open - RAL 7035</b>
		External dimensions
		Height (mm)   Width (mm)
20	0 365 80	235   340
20	0 365 81	165   260
		Internal dimensions
		Height (mm)   Width (mm)   Depth (mm)
		200   310   18
		130   230   18
		<b>Closed - RAL 7035</b>
1	0 365 82	Rigid, plastic, IP 50 Internal dimensions: 324 x 120 x 18 mm
		<b>Transparent</b>
10	0 097 99	Soft plastic, A4 - 305 x 220 mm
		<b>Rail height spacer</b>
1	3 382 40	Used to combine modular devices and DPX <sup>3</sup> 160/250 on the same rail
1	3 382 41	Used to combine modular devices and DRX on the same rail
1	3 382 42	Used to combine DRX and DPX <sup>3</sup> 160/250 on the same rail
		<b>White RAL 9003 blanking plates</b>
20	0 016 60	5 modules. Separable into modules or half-modules
20	3 397 54	24 modules, untapped blanking panel which can be cut as required
		<b>Clip-on holders for self-adhesive labels</b>
		Supplied with sheet of labels for marking rows on faceplate
10	3 397 55	24 modules
10	3 397 56	36 modules
		<b>Connection of protective conductors</b>
		<b>Additional brass bar</b>
		For protective conductor. Fits onto functional uprights using the lugs supplied
1	0 373 00	For 24-module width cabinet
1	3 397 57	For 36-module width cabinet
		<b>Equipotential link conductor</b>
1	3 397 53	Length 350 mm. Cross-section 6 mm <sup>2</sup>