

Rittal – The System.

Faster – better – everywhere.

Lock insert – SZ 2462.000

Date : Nov 27, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Lock insert – SZ 2462.000

created: 27.11.2019 on www.rittal.com/com-en



Product description

Design: A

Material: Die-cast zinc

Product features

To fit:

- Enclosure type: AX with cam
- Enclosure type: AX with 3-point lock system
- Enclosure type: KXE-Box
- Enclosure type: PC enclosure keyboard drawer or fold-out tray
- Enclosure type: TP desk section and console
- Enclosure type: TP universal console
- Enclosure type: One-piece console - console cover
- Enclosure type: One-piece console TP - Console door
- Enclosure type: EB
- Enclosure type: BG with cam
- Enclosure type: AE with cam
- Enclosure type: Based on AE with cam
- Enclosure type: Wall-mounted enclosure AE with cam
- Enclosure type: AE with 3-point lock
- Enclosure type: Based AE with 3-point lock
- Enclosure type: Wall-mounted enclosure AE with 3-point lock
- Enclosure type: EL 3-part, 6 – 15 U

Dimensions: Length: 27 mm

Installation in handle system:

- Comfort handle AX
- Mini-comfort handle AX
- Ergoform-S handle Standard
- Ergoform-S handle Standard for KS plastic enclosures
- Adjacent door latch

Lock insert: 7 mm triangular

Packs of:	1 pc(s).
Weight/pack:	0.02 kg
Copper weight (kg per piece):	0
EAN:	4028177023802
Customs tariff number:	83015000
ETIM 7.0:	EC000743
ETIM 6.0:	EC000743
eCl@ss 8.0/8.1:	27409218
eCl@ss 6.0/6.1:	27409218
Product description:	SZ Lock insert, version A, Die-cast zinc, 7 mm triangular, L: 27 mm
Approvals	
Certificates:	EAC