

Rittal – The System.

Faster – better – everywhere.

Stepped collar – SZ 2899.320

Date : Jan 3, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Stepped collar – SZ 2899.320

created: 03.01.2020 on www.rittal.com/com-en



Product description

Description: For cable entry, simply cut off at the required level to match the cable diameter.

Applications: For wall thicknesses from 1.5 to 4.5 mm

Material: Plastic to UL 94-HB

**Protection category
IP to IEC 60 529:** IP 54 with careful cable entry

Product features

Thread: Type: M32

**For material
thicknesses:** 1,5 mm - 4,5 mm

Packs of: 25 pc(s).

Weight/pack: 0.15 kg

**Copper weight (kg
per piece):** 0

EAN: 4028177389625

**Customs tariff
number:** 39269097

ETIM 7.0: EC000879

ETIM 6.0: EC000879

eCl@ss 8.0/8.1:	27069216
eCl@ss 6.0/6.1:	27400604
Product description:	SZ Stepped collar, for wall thickness from 1,5 bis 4,5 mm, for hole M32, Sealing range: 13-26.5 mm
Approvals	
Certificates:	EAC