



Main

Range of product	Acti 9
Product name	Acti 9 iPC
Product or component type	Modular socket-outlet
Device short name	IPC
Poles description	2P + E
Outlet standard	German

Complementary

[In] rated current	16 A
[Ue] rated operational voltage	250 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
9 mm pitches	5
Height	84 mm
Width	45 mm
Depth	63 mm
Product weight	98 g
Colour	White
Connections - terminals	Tunnel type terminal 1 cable(s) flexible 6 mm ² Tunnel type terminal 1 cable(s) rigid 10 mm ²
Wire stripping length	13 mm
Tightening torque	1.2 N.m

Environment

Standards	VDE 0620
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
IK degree of protection	IK03
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-25...70 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
