

## Product data sheet

### Characteristics

# XALD05

tamno sivi poklopac praznog kućišta sa svijetlo sivom bazom – 5 otvora



### Main

Range of product	Harmony XALD
Product or component type	Empty control station
Device short name	XALD
Product destination	For XB5 Ø 22 mm control and signalling units
Number of cut-out	5 cut-outs
Colour of base of enclosure	Light grey RAL 7035)
Colour of cover	Dark grey RAL 7016)
Material	Polycarbonate
Cable entry	2 knock-outs for cable entry 14 mm 2 knock-outs for Pg 13 cable gland and ISO M20 12 mm
IP degree of protection	IP66 IEC 60529 IP67 IP69 IP69K

### Complementary

Assembly style	For customer assembly
Number of horizontal rows	1
Number of vertical rows	5
Net weight	0,322 kg
Resistance to high pressure washer	7000000 Pa 55 °C 0.1 m
Mounting of block	Rear mounting Front mounting
Electrical composition code	SR2 PR1 SR1 MR1 MF2 MF1 SF1 PF2 PF1 SF2
Main group	5 cut-outs
Group of product	Standard grey

### Environment

Protective treatment	TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-40...70 °C
Overvoltage category	Class II IEC 60536
NEMA degree of protection	NEMA 13 NEMA 4X

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

IK degree of protection	IK03 EN 50102
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1 CSA C22.2 No 14 JIS C8201-5-1 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-5-5 JIS C8201-1

### Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACh	<a href="#">Izjava REACh</a>
REACh, bez SVHC	Da
Direktiva EU RoHS	Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	<a href="#">Da</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS Za Kinu</a>
Izjava o očuvanju okoliša	<a href="#">Ekološki Profil Proizvoda</a>
Profil cirkularnosti	<a href="#">Informacije O Kraju Vijeka Trajanja</a>

### Contractual warranty

Jamstvo	18 months
---------	-----------