

## Product data sheet

### Characteristics

## XB4BV33

zelena potpuna signalna žaruljica Ø22 obična  
leća sa žaruljicom BA9s 110... 120V



### Main

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Range of product                | Harmony XB4                         |
| Product or component type       | Pilot light                         |
| Device short name               | XB4                                 |
| Bezel material                  | Chromium plated metal               |
| Fixing collar material          | Zamak                               |
| Head type                       | Standard                            |
| Mounting diameter               | 22 mm                               |
| Sale per indivisible quantity   | 1                                   |
| Shape of signaling unit head    | Round                               |
| Cap/operator or lens colour     | Green                               |
| Operator additional information | With plain lens                     |
| Light source                    | Incandescent                        |
| Bulb base                       | BA 9s                               |
| Light block supply              | Via integral transformer 1,2 VA 6 V |
| [Us] rated supply voltage       | 110...120 V AC 50/60 Hz             |

### Complementary

|                                        |                                                                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height                                 | 47 mm                                                                                                                                                 |
| Width                                  | 30 mm                                                                                                                                                 |
| Depth                                  | 78 mm                                                                                                                                                 |
| Terminals description ISO n°1          | (X1-X2)PL                                                                                                                                             |
| Net weight                             | 0,152 kg                                                                                                                                              |
| Resistance to high pressure washer     | 7000000 Pa 55 °C 0.1 m                                                                                                                                |
| Connections - terminals                | Screw clamp terminals, <= 2 x 1.5 mm² with cable end EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.22...2 x 2.5 mm² without cable end EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 600 V 3)EN 60947-1                                                                                                                                    |
| [Uimp] rated impulse withstand voltage | 6 kV EN 60947-1                                                                                                                                       |
| Signalling type                        | Steady                                                                                                                                                |
| Device presentation                    | Complete product                                                                                                                                      |

### Environment

|                                       |                                         |
|---------------------------------------|-----------------------------------------|
| Protective treatment                  | TH                                      |
| Ambient air temperature for storage   | -40...70 °C                             |
| Ambient air temperature for operation | -40...55 °C                             |
| Electrical shock protection class     | Class I IEC 60536                       |
| IP degree of protection               | IP66 IEC 60529<br>IP67<br>IP69<br>IP69K |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                      |

|                         |                                                                                                                                         |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| IK degree of protection | IK06 IEC 50102                                                                                                                          |
| Standards               | JIS C8201-5-1<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>CSA C22.2 No 14<br>EN/IEC 60947-1<br>JIS C8201-1 |
| Product certifications  | CSA<br>UL listed                                                                                                                        |
| Vibration resistance    | 5 gn 12...500 Hz)IEC 60068-2-6                                                                                                          |
| Shock resistance        | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |

## Offer Sustainability

|                            |                                                                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                                                               |
| Uredba REACh               | <a href="#">Izjava REACh</a>                                                                                                                         |
| REACh, bez SVHC            | Da                                                                                                                                                   |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a>                                             |
| Bez žive                   | Da                                                                                                                                                   |
| Informacije o RoHS izuzeću | <a href="#">Da</a>                                                                                                                                   |
| Propis RoHS za Kinu        | <a href="#">Izjava RoHS Za Kinu</a>                                                                                                                  |
| Izjava o očuvanju okoliša  | <a href="#">Ekološki Profil Proizvoda</a>                                                                                                            |
| Profil cirkularnosti       | <a href="#">Informacije O Kraju Vijeka Trajanja</a>                                                                                                  |
| WEEE                       | Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom. |

## Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|