

Product data sheet

Characteristics

XB5KS2G4

continuous or intermittent illuminated red
buzzer 110...120 v ac/dc



Main

Range of product	Harmony XB5
Bezel material	Plastic
Product or component type	Annunciator
Mounting diameter	22 mm
Cap/operator or lens colour	Red

Complementary

[Us] rated supply voltage	110...120 V +/- 10 %
Supply circuit type	AC/DC
Supply frequency	50/60 Hz
Current consumption	<= 20 mA
Signalling type	Continuous or intermittent tone
Resistance to high pressure washer	9000000 Pa 82 °C 0.1 m
Height	29 mm
Width	29 mm
Depth	55 mm
Net weight	0,024 kg

Environment

Noise level	90 dB 0.1 m
Protective treatment	TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-40...70 °C
Overvoltage category	Class II IEC 60536
IP degree of protection	IP66 IEC 60529 IP67 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK03 EN 50102 IK03 IEC 50102

Standards	IEC 60947-5-4 UL 508 JIS C8201-5-1 EN 60947-5-4 CSA C22.2 No 14 EN 60947-5-1 IEC 60947-5-1 EN 60947-1 IEC 60947-1 JIS C8201-1
Product certifications	GL CSA UL listed LROS (Lloyds register of shipping) BV DNV RINA

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
Direktiva EU RoHS	Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
Izjava o očuvanju okoliša	Ekološki Profil Proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.