



Main

Product or component type	Mini trunking
Colour tint	White RAL 9010
Quantity per set	154 m

Complementary

Trunking material	Plastic
Compartment partitioning	1 compartment
Trunking dimension	12 x 7 mm
Fixing mode	Power cable : screw-fixed Low voltage cable : adhesive tape Pre-punched fixing hole with distance of 230 mm between centers
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	12 mm
Width	7 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-5...60 °C
Environmental health and issues	Cadmium free Lead free
Product certifications	Low voltage directive 2006/95/EC
Standards	EN 50085-1 : 2005 EN 50085-2-1 : 2006

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 1826 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------