



Main

| | |
|---------------------------|--------------------|
| Product or component type | Mini trunking |
| Device application | Cable distribution |
| Colour tint | White RAL 9010 |
| Quantity per set | 156 m |

Complementary

| | |
|--------------------------|---|
| Trunking material | Plastic |
| Compartment partitioning | 1 compartment |
| Trunking dimension | 16 x 16 mm |
| Fixing mode | Power cable : screw-fixed Low voltage cable : adhesive tape Pre-punched fixing hole with distance of 230 mm between centers |
| Material | PVC (polyvinyl chloride) |
| Length | 2000 mm |
| Height | 16 mm |
| Width | 16 mm |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -5...60 °C |
| Environmental health and issues | Lead free Cadmium free |
| Standards | EN 50085-1 : 2005 EN 50085-2-1 : 2006 |

Offer Sustainability

| | |
|--------------------------|-----------------------|
| Sustainable offer status | Green Premium product |
|--------------------------|-----------------------|

| | |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1826 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|