

## Product data sheet

### Characteristics

## ZB5AH03

glava zelenog upuštenog tipkala Ø 22 potisno-  
potisna neoznačena



### Main

|                               |                                      |
|-------------------------------|--------------------------------------|
| Range of product              | Harmony XB5                          |
| Product or component type     | Head for non-illuminated push-button |
| Device short name             | ZB5                                  |
| Bezel material                | Dark grey plastic                    |
| Mounting diameter             | 22 mm                                |
| Head type                     | Standard                             |
| Sale per indivisible quantity | 1                                    |
| Shape of signaling unit head  | Round                                |
| Type of operator              | push-push                            |
| Operator profile              | Green flush, unmarked                |

### Complementary

|                             |                                                                                                                                                       |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 29 mm                                                                                                                                                 |
| CAD overall height          | 29 mm                                                                                                                                                 |
| CAD overall depth           | 28 mm                                                                                                                                                 |
| Net weight                  | 0,018 kg                                                                                                                                              |
| Mechanical durability       | 500000 cycles                                                                                                                                         |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                            |
| Electrical composition code | C11 3 single front mounting<br>C15 1 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting<br>C9 3 single front mounting |
| Device presentation         | Basic element                                                                                                                                         |

### Environment

|                                       |                                                                                                                     |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                  |
| Ambient air temperature for storage   | -40...70 °C                                                                                                         |
| Ambient air temperature for operation | -40...70 °C                                                                                                         |
| Overvoltage category                  | Class II IEC 60536                                                                                                  |
| IP degree of protection               | IP66 IEC 60529<br>IP69<br>IP69K                                                                                     |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                  |
| Resistance to high pressure washer    | 7000000 Pa 55 °C 0.1 m                                                                                              |
| IK degree of protection               | IK05 IEC 50102                                                                                                      |
| Standards                             | UL 508<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>JIS C8201-1 |

|                        |                                                                                                                    |
|------------------------|--------------------------------------------------------------------------------------------------------------------|
| Product certifications | DNV<br>UL listed<br>RINA<br>GL<br>BV<br>LROS (Lloyds register of shipping)<br>CSA                                  |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                      |

### Offer Sustainability

|                            |                                                                                                                                                                                            |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                                                                                                     |
| Uredba REACH               |  <a href="#">Izjava REACH</a>                                                                             |
| REACH, bez SVHC            | Da                                                                                                                                                                                         |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS)  <a href="#">Izjava EU RoHS</a> |
| Bez otrovnih teških metala | Da                                                                                                                                                                                         |
| Bez žive                   | Da                                                                                                                                                                                         |
| Informacije o RoHS izuzeću |  <a href="#">Da</a>                                                                                       |
| Propis RoHS za Kinu        |  <a href="#">Izjava RoHS Za Kinu</a>                                                                      |
| Izjava o očuvanju okoliša  |  <a href="#">Ekološki Profil Proizvoda</a>                                                                |
| Profil cirkularnosti       |  <a href="#">Informacije O Kraju Vijeka Trajanja</a>                                                      |

### Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|