

## Product data sheet

### Characteristics

## ZB5AP3S

glava zelenog upuštenog tipkala Ø 22 opružni  
povrat neoznačena



### Main

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Range of product                | Harmony XB5                          |
| Product or component type       | Head for non-illuminated push-button |
| Device short name               | ZB5                                  |
| Product compatibility           | Legend holder                        |
| Bezel material                  | Dark grey plastic                    |
| Mounting diameter               | 22 mm                                |
| Head type                       | Standard                             |
| Sale per indivisible quantity   | 1                                    |
| Shape of signaling unit head    | Round                                |
| Type of operator                | Spring return                        |
| Operator profile                | Green flush, unmarked                |
| Operator additional information | Coloured boot                        |

### Complementary

|                             |                                                                                                                                                                                                |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 30 mm                                                                                                                                                                                          |
| CAD overall height          | 30 mm                                                                                                                                                                                          |
| CAD overall depth           | 33 mm                                                                                                                                                                                          |
| Net weight                  | 0,021 kg                                                                                                                                                                                       |
| Mechanical durability       | 10000000 cycles                                                                                                                                                                                |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                     |
| Electrical composition code | C1 9 single front mounting<br>C2 9 single and double front mounting<br>C11 3 single front mounting<br>C15 1 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting |
| Device presentation         | Basic element                                                                                                                                                                                  |

### Environment

|                                       |                                                                       |
|---------------------------------------|-----------------------------------------------------------------------|
| Protective treatment                  | TH                                                                    |
| Ambient air temperature for storage   | -40...70 °C                                                           |
| Ambient air temperature for operation | -40...70 °C                                                           |
| Overvoltage category                  | Class II IEC 60536                                                    |
| IP degree of protection               | IP66 IEC 60529<br>IP67 IEC 60529<br>IP69 IEC 60529<br>IP69K ISO 20653 |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                    |
| Resistance to high pressure washer    | 7000000 Pa 55 °C 0.1 m                                                |
| IK degree of protection               | IK03 IEC 50102                                                        |

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Standards              | CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>JIS C8201-5-1<br>UL 508<br>EN/IEC 60947-1<br>JIS C8201-1 |
| Product certifications | BV<br>RINA<br>DNV<br>CSA<br>LROS (Lloyds register of shipping)<br>UL listed<br>GL                                   |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |
| Vibration resistance   | 5 gn 2...500 Hz) IEC 60068-2-6                                                                                      |

## Offer Sustainability

|                            |                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------|
| Status održive ponude      | Proizvod Green Premium                                                                                   |
| Uredba REACh               | <a href="#">Izjava REACh</a>                                                                             |
| REACh, bez SVHC            | Da                                                                                                       |
| Direktiva EU RoHS          | Proaktivna sukladnost (proizvod izvan zakonskog okvira direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Bez otrovnih teških metala | Da                                                                                                       |
| Bez žive                   | Da                                                                                                       |
| Informacije o RoHS izuzeću | <a href="#">Da</a>                                                                                       |
| Propis RoHS za Kinu        | <a href="#">Izjava RoHS Za Kinu</a>                                                                      |
| Izjava o očuvanju okoliša  | <a href="#">Ekološki Profil Proizvoda</a>                                                                |
| Profil cirkularnosti       | <a href="#">Informacije O Kraju Vijeka Trajanja</a>                                                      |

## Contractual warranty

|         |           |
|---------|-----------|
| Jamstvo | 18 months |
|---------|-----------|