

Rittal – The System.

Faster – better – everywhere.

Busbar support – SV 3052.000

Date : Nov 28, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Busbar support – SV 3052.000

created: 28.11.2019 on www.rittal.com/com-en



Product description

| | |
|---------------------------|---|
| Material: | Fibreglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0 |
| Colour: | RAL 7035 |
| Note on Model No.: | The base component of the busbar support may also be used as a single-pole support. |

Product features

| | |
|---|--|
| To fit busbars: | Type: Busbar E-Cu with cross-section width: 50 mm with cross-section width: 60 mm with cross-section width: 80 mm with cross-section height: 10 mm with cross-section height: 10 mm with cross-section height: 10 mm |
| Number of poles: | 3-pole |
| Centre-to-centre spacing of busbars: | 185 mm |
| Dimensions: | Width: 24 mm Height: 515 mm Depth: 51 mm |
| Rated current max.: | 1600 A |
| Packs of: | 2 pc(s). |
| Weight/pack: | 1.34 kg |

| | |
|--------------------------------------|---|
| Copper weight (kg per piece): | 0 |
| EAN: | 4028177035751 |
| Customs tariff number: | 85469010 |
| ETIM 7.0: | EC001166 |
| ETIM 6.0: | EC001166 |
| eCl@ss 8.0/8.1: | 27400607 |
| eCl@ss 6.0/6.1: | 27400613 |
| Product description: | SV Busbar support, 3-pole, 185 mm bar centre distance, for busbar WH: 50-80x10 mm |
| Approvals | |
| Approvals: | ABS |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |