



Main

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact NS630b...1600 Compact NS1600b...3200 Compact INS Compact INSE Compact INSJ Compact INV Compact NG Compact NR Compact NSX EasyPact CVS
Offer type	C5 C4
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-make Early-break
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12 6 A 110 V AC 50/60 Hz AC-12 6 A 220/240 V AC 50/60 Hz AC-12 6 A 24 V AC 50/60 Hz AC-12 6 A 380/440 V AC 50/60 Hz AC-12 6 A 48 V AC 50/60 Hz AC-12 6 A 480 V AC 50/60 Hz AC-12 6 A 660/690 V AC 50/60 Hz AC-15 0,1 A 660/690 V AC 50/60 Hz

AC-15 1,5 A 480 V AC 50/60 Hz
 AC-15 2 A 380/440 V AC 50/60 Hz
 AC-15 4 A 220/240 V AC 50/60 Hz
 AC-15 5 A 110 V AC 50/60 Hz
 AC-15 6 A 24 V AC 50/60 Hz
 AC-15 6 A 48 V AC 50/60 Hz
 DC-12 0,3 A 250 V DC
 DC-12 0,6 A 110 V DC
 DC-12 2,5 A 48 V DC
 DC-12 6 A 24 V DC
 DC-14 0,03 A 250 V DC
 DC-14 0,05 A 110 V DC
 DC-14 0,2 A 48 V DC
 DC-14 1 A 24 V DC

Minimum load	100 mA 24 V
Width	1 cm
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-25...70 °C

Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	Izjava REACH
REACH, bez SVHC	Da
Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez otrovnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS za Kinu Proaktivna izjava RoHS za Kinu (izvan pravnog dosega propisa RoHS za Kinu)
Izjava o očuvanju okoliša	Ekološki profil proizvoda
Profil cirkularnosti	Nema potrebe za specifičnim operacijama recikliranja

Contractual warranty

Jamstvo	18 months
---------	-----------